

Implen NanoPhotometer® N50-Touch Used for Supporting COVID-19 Testing



The global COVID-19 pandemic has affected nearly every country in the World – changing how we live, work and the way we interact. Now more than ever, countries are looking to their researchers and scientists for solutions and a path for moving forward. New mobile labs and testing facilities are being established in countries across the world.

The spread of COVID-19 in Indonesia is occurring at a rapid rate. Indonesia now has one of the highest numbers of confirmed COVID-19 cases in all of Southeast Asia, according to numbers released by their government. To help prevent further spread and facilitate the detection of COVID-19 in the community, the State Intelligence Agency/Badan Intelijen Negara (BIN) of the Republic of Indonesia has established mobile laboratories for COVID-19 testing. The first four of the new mobile labs have been dedicated to serving communities where COVID-19 cases are most prevalent.



Each mobile laboratory consists of equipment for extracting COVID-19 samples and instruments for viral detection using Real Time PCR method. One of the supporting instruments in the mobile laboratory is the Implen NanoPhotometer® N50-Touch. The N50-Touch UV/VIS spectrophotometer is used for detecting the concentration of extracted viral RNA prior to Real Time RT-PCR. The Indonesian government (through BIN) purchased a total of 4 NanoPhotometer® N50-Touch to outfit their mobile labs. Implen's distribution partner in Indonesia, Pt. GeneCraft Labs is providing comprehensive workflow solutions to BIN and is installing the NanoPhotometer® instruments.



The NanoPhotometer® N50-Touch was chosen as the best fit for the BIN labs due to the instruments' accuracy and consistent measurement results. The device is trusted by researchers worldwide to provide comprehensive measurement data. Additionally, the NanoPhotometer® is easy to use with an intuitive user interface and multiple options for quick data transfer.



Microvolume Capability

Starting with only 0.3 µl of sample



Scan

2.5 - 4 seconds per reading
200 to 650 nm
Resolution 5 nm



Certainty in Real Time

Impurity and air bubble recognition with Sample Control™ and Blank Control™



WiFi HotSpot LAN



Endless Connectivity

Built-in File Server for data access from Windows and Mac computers
Print to Airprint™ & HP Universal Driver compatible printers as well as DYMO Label printers
REST API for LIMS integration



Flexible Unit Control and Ultimate Data Security

Computer (Windows & Mac)
Built-in touchscreen
Smartphone / Tablet (Android OS & iOS)
Proprietary NPOS immune to known threats

World's smallest footprint in its class: only 20 x 20 x 12 cm
No reconditioning, no recalibration and no regular maintenance ever
Stand-alone operation with built-in 7" glove compatible touch screen
Universal data output: Excel and PDF | Multi Language User Interface | Barcode ready | 32 GB of onboard memory